

Chalet

20 mm tongue/groove

Technical information	
Produced according to:	European parquet norm EN 13489 - 2017
Dimension:	20 x 200/ 250/ 300/ 350/ 395 x 2000 - 4000 mm
Toplayer:	about 4.5 mm
Construction:	3-layer construction; Hardwood toplayer, middlelayer and bottomlayer made of spruce Toplayer about 4.5 mm Middlelayer 10.5 mm Bottomlayer 5.0 mm
Boards/ m ² per carton:	-
Cartons/ m ² per pallet:	-
Slotted top layers per carton/ minimum length (mm):	-
Weight per carton/ pallet in kg:	-
Floor heating systems:	Well suitable
Fire behavior ¹⁾ :	Dfl-s1
Content of formaldehyd ²⁾ :	E1
Content of pentachlorophenol (PCP) ²⁾ :	no performance detected
Density kg/ m ³ ²⁾ :	about 600
Antislip performance:	Live Natural USRV 40 ²⁾
Abrasion resistance:	-
Thermal conductivity ²⁾ :	0.15 W/ (m·K)
Areal thermal resistance ³⁾ :	0.133 m ² · K/ W



DOP 4658



www.blauer-engel.de/uz176

CE
BOEN AS
EN 14342



¹⁾ according to DIN EN 13501-1, ²⁾ according to DIN 14342, ³⁾ according to ENV 13696,

⁴⁾ according to DIN 68861, ⁵⁾ according to EN 12524