

Plank Castle

14 mm tongue/ groove



Technical information	
Produced according to:	European parquet norm EN 13489 - 2017
Dimension:	14 x 209 x 2200 mm
Toplayer:	about 3.5 mm
Construction:	3-layer construction; Hardwood toplayer, middlelayer and bottomlayer made of spruce Toplayer about 3.5 mm Middlelayer 8.8 mm Bottomlayer 1.7 mm
Boards/ m ² per carton:	6/ 2.76
Cartons/ m ² per pallet:	50/ 138
Slotted top layers per carton/ minimum length (mm):	-
Weight per carton/ pallet in kg:	21.5/ 1075
Floor heating systems:	Well suitable to very well suitable
Fire behavior ¹⁾ :	Cfl-s1 and Dfl-s1 depending on wood specie and surface treatment
Content of formaldehyd ²⁾ :	E1
Content of pentachlorophenol (PCP) ²⁾ :	no performance detected
Density kg/ m ³ ²⁾ :	about 600
Antislip performance:	Live Matt USRV 33 ⁶⁾ R9 ⁷⁾ Live Natural sanded USRV 59 ⁶⁾ R10 ⁷⁾ Live Natural brushed USRV 45 ⁶⁾ R10 ⁷⁾ Live Pure brushed USRV 91 ⁶⁾ R11 ⁷⁾
Abrasion resistance:	Live Matt 70/ 1100 ³⁾ Live Matt 100 ⁴⁾
Thermal conductivity ²⁾ :	0.15 W/ (m·K)
Areal thermal resistance ⁵⁾ :	0.093 m ² · K/ W



DOP 4658



www.blauer-engel.de/uz176



¹⁾ according to DIN EN 13501-1, ²⁾ according to DIN 14342, ³⁾ according to ENV 13696, ⁴⁾ according to DIN 68861,

⁵⁾ according to EN 12524, ⁶⁾ according to CEN/TS 15676, ⁷⁾ according to DIN EN 51130