

PLANK FINELINE 14 mm Clic

Technical information:

Produced according to:	European parquet norm EN 13489 - 2017	
Dimension:	14 x 138 x 2200 mm	
Toplayer:	ca. 3.5 mm	
Construction:	3-layer construction; Hardwood toplayer, middlelayer and bottomlayer made of spruce Toplayer about 3.5 mm Middlelayer 8.8 mm Bottomlayer 1.7 mm	
Boards / m² per carton:	10/ 3.04	
Cartons/ m² per pallet:	42/ 127.68	
Slotted top layers per carton/ minimum length (mm):	-	
Weight per carton/ pallet in kg:	25.5/ 1071	
Floor heating systems:	Well suitable to very well suitable	
Fire behavior ¹⁾:	Cfl-s1 and Dfl-s1 depending on wood specie and surface treatment	
Content of formaldehyd ²⁾:	E1	
Content of pentachlorophenol (PCP) ²⁾:	non performance detected	
Density kg/ m³ ²⁾:	about 600	
Antislip performance:	Live Satin	USRV 25 ²⁾
	Live Matt	USRV 29 ²⁾
	Live Natural	USRV 40 ²⁾
Abrasion resistance:	Live Satin	70/ 1100 ³⁾
	Live Satin	100 ⁴⁾
Thermal conductivity ²⁾:	0.15 W/ (m·K)	
Areal thermal resistance ⁵⁾:	0.093 m ² · K/ W	



BOEN AS
 EN 14342
 DOP 4658



www.blauer-engel.de/uz176



¹⁾ according to DIN EN 13501-1, ²⁾ according to DIN 14342, ³⁾ according to ENV 13696, ⁴⁾ according to DIN 68861, ⁵⁾ according to EN 12524