

TRAFFIC 12.5 mm tongue/ groove

Technical information:

Produced according to:	European parquet norm EN 13489 - 2017	
Dimension:	12.5 x 70 x 590 mm	
Toplayer:	about 5.5 mm	
Construction:	2-layer construction; Hardwood top layer, Bottom layer made of spruce Top layer: approx. 5.5 mm Bottom layer: 7.0 mm	
Boards/ m² per carton:	26 left and 26 right strips/ 2.15	
Cartons/ m² per pallet:	36/ 77.4	
Divided strips per carton/ minimum length (mm):	2/ 295	
Weight per carton/ pallet in kg:	15.5/ 558	
Floor heating systems:	Very well suitable	
Fire behaviour ¹⁾:	Cfl-s1 depending on wood species and surface treatment.	
Content of formaldehyde ²⁾:	E1	
Content of pentachlorophenol (PCP) ²⁾:	non performance detected	
Density kg/ m³ ²⁾:	about 600	
Antislip performance:	Live Satin	USRV 25 ²⁾
	Live Matt	USRV 29 ²⁾
	Live Natural	USRV 40 ²⁾
Abrasion resistance:	Live Satin	70/ 1100 ³⁾
	Live Satin	100 ⁴⁾
Thermal conductivity ²⁾:	0.15 W/ (m·K)	
Areal thermal resistance ⁵⁾:	0.083 m ² · K/ W	



BOEN AS
EN 14342
DOP 4658



www.blauer-engel.de/uz176



¹⁾ according to DIN EN 13501-1, ²⁾ according to DIN 14342, ³⁾ according to ENV 13696, ⁴⁾ according to DIN 68861, ⁵⁾ according to EN 12524