

Maxi

10.5 mm tongue/groove



Technical information	
Produced according to:	European parquet norm EN 13489 - 2017
Dimension:	10.5 x 100 x 833/ 1000 mm
Toplayer:	about 3.5 mm
Construction:	2-layer construction; Hardwood toplayer and bottomlayer made of spruce Toplayer about 3.5 mm Bottomlayer 7.0 mm
Boards/ m² per carton:	1000 mm: 26 pieces right-hand strips/ 2.6 833 mm: 20 pieces right-hand strips/ 1,667
Cartons/ m² per pallet:	1000 mm: 32/ 83.2 833 mm: 50/ 83,35
Divided top layers per carton/ minimum length (mm):	2/ 500
Weight per carton/ pallet in kg:	1000 mm: 15/ 480 833 mm: 9,35/ 468
Floor heating systems:	Very well suitable
Fire behavior ¹⁾:	Cfl-s1 and Dfl-s1 depending on wood specie and surface treatment.
Content of formaldehyd ²⁾:	E1
Content of pentachlorophenol (PCP) ²⁾:	no performance detected
Density kg/ m³ ²⁾:	about 600
Antislip performance:	Live Satin USRV 25 ²⁾ Live Matt USRV 29 ²⁾ Live Natural USRV 40 ²⁾
Abrasion resistance:	Live Satin 70/ 1100 ³⁾ Live Satin 100 ⁴⁾
Thermal conductivity ²⁾:	0.15 W/ (m·K)
Areal thermal resistance ⁵⁾:	0.07 m ² · K/ W



Toplayer: Hardwood
Bottomlayer: Spruce

DOP 4658



www.blauer-engel.de/uz176

CE
BOEN AS
EN 14342



¹⁾ according to DIN EN 13501-1, ²⁾ according to DIN 14342, ³⁾ according to ENV 13696,

⁴⁾ according to DIN 68861, ⁵⁾ according to EN 12524