

Traffic

12.5 mm tongue/groove



Technical information	
Produced according to:	European parquet norm EN 13489 - 2017
Dimension:	12.5 x 70 x 470 mm
Toplayer:	about 5.5 mm
Construction:	2-layer construction; Hardwood toplayer and bottomlayer made of spruce Toplayer about 5.5 mm Bottomlayer 7.0 mm
Boards/ m ² per carton:	34 pieces right-hand strips/ 34 pieces left-hand strips/ 2.24
Cartons/ m ² per pallet:	36/ 80.64
Divided top layers per carton/ minimum length (mm):	2/ 295
Weight per carton/ pallet in kg:	16.5/ 594
Floor heating systems:	Very well suitable
Fire behavior ¹⁾ :	Cfl-s1 depending on wood specie and surface treatment.
Content of formaldehyd ²⁾ :	E1
Content of pentachlorophenol (PCP) ²⁾ :	no performance detected
Density kg/ m ³ ²⁾ :	about 600
Antislip performance:	Live Satin USRV 25 ²⁾ Live Matt USRV 29 ²⁾ Live Natural USRV 40 ²⁾
Abrasion resistance:	Live Satin 70/ 1100 ³⁾ Live Satin 100 ⁴⁾
Thermal conductivity ²⁾ :	0.15 W/ (m·K)
Areal thermal resistance ⁵⁾ :	0.083 m ² · K/ W



Toplayer: Hardwood
Bottomlayer: Spruce

DOP 4658



www.blauer-engel.de/uz176

CE
BOEN AS
EN 14342



¹⁾ according to DIN EN 13501-1, ²⁾ according to DIN 14342, ³⁾ according to ENV 13696,

⁴⁾ according to DIN 68861, ⁵⁾ according to EN 12524