

# Herringbone T/G 10.5 × 137

## Technical Information

Produced according to	European parquet norm EN 13489 - 2017
Structure	2-layer parquet <b>Top layer</b> made of hardwood: ca. 3.5 mm <b>Bottom layer</b> made of spruce: 7.0 mm
Dimension	10.5 × 137 × 790 mm
Connection	Tongue / groove
Type of wood (Top layer)	Oak
Color	Transparent, Soft Brown, Pale White, white
Grading	Adagio, Andante, Animoso, Vivo
Surface	Live Matt, Live Matt Plus, Live Natural
Surface structure	brushed, sanded
Bevel	4V bevel
Boards/m <sup>2</sup> per carton	15 right hand strips, 15 left hand strips / 3.25
Cartons/m <sup>2</sup> per pallet	32 / 104
Slotted top layers per carton / minimum length (mm)	0
Weight per carton / pallet in kg	19 / 608
Floor heating systems	very well suitable
Fire behavior <sup>1)</sup>	Dfl-s1
Content of formaldehyde <sup>2)</sup>	E1
Content of pentachlorophenol (PCP) <sup>2)</sup>	≤ 5 × 10 <sup>-6</sup> n
Density kg/m <sup>3</sup> <sup>2)</sup>	ca. 500
Thermal conductivity <sup>2)</sup>	0,132 W/ (m × K)
Areal thermal resistance <sup>2)</sup>	0,079 m <sup>2</sup> × K/W

	brushed	Live Matt	Live Matt Plus	Live Natural	Live Pure
Antislip performance		USRV 39 <sup>3)</sup> R10 <sup>4)</sup>	USRV 57 <sup>3)</sup> R10 <sup>4)</sup>	USRV 60 <sup>3)</sup> R10 <sup>4)</sup>	USRV 94 <sup>3)</sup> R10 <sup>4)</sup>
	sanded	Live Matt	Live Matt Plus	Live Natural	Live Pure
Antislip performance		USRV 44 <sup>3)</sup> R10 <sup>4)</sup>	USRV 42 <sup>3)</sup> R10 <sup>4)</sup>	USRV 71 <sup>3)</sup> R11 <sup>4)</sup>	USRV 99 <sup>3)</sup> R10 <sup>4)</sup>

